



# LIGHT VEHICLE MODULE - FUEL

DELIVERS UP TO 7,000L OF DIESEL, GASOLINE,  
OR NATO STANDARD FUELS.



Demountable fuel delivery and dispensing system with integrated pumping system.

Transportable by MRAP utility vehicles, 4X4 and 6X6 logistics vehicles.

Compatible with on-board vehicle crane or forklift handling systems.

Very low profile system for ultimate mobility in tough terrains.

Ballistic protection for forward area operations.

[HIGHLY CUSTOMIZABLE TO MEET YOUR REQUIREMENTS](#)

## INTERMODAL



## BASE SPECIFICATION

<b>Length</b>	2,991 - 4,579 mm / 10' - 15'
<b>Width</b>	2,438 mm / 8'
<b>Height</b>	1,220 - 1,727 mm / 4'0" - 5'8"
<b>Payload range</b>	3,000 - 7,000 litres / 850 - 1,840 U.S. gallon
<b>Tare range (typical)</b>	1,140 - 2,200 kg / 2,500 - 4,840 lbs
<b>Max. gross range</b>	3,500 - 9,000 kg / 4,400 - 22,000 lbs
<b>Stacking</b>	192,000 kg / 423,320 lbs
<b>Build codes</b>	AD-Merkblätter, WHG, VAWs, BetrSichV
<b>Transport codes (Road, Rail, Sea)</b>	ADR, RID, IMDG (T2-T10), IATA, Customs, Lloyd's Register, BAM, ISO 1496/3, UIC 592-2 (as far as applicable), CSC, ISO 3874
<b>Materials</b>	1.4301/1.4404 stainless steel. Double-shell design option.
<b>Working pressure</b>	1.5 - 4.0 bar / 22.5 - 60 psi
<b>Temperature range (inner)</b>	-40 -+ 50 °C / -40 -+ 122 °F
<b>Optional equipment</b>	<ul style="list-style-type: none"> <li>Single/double-shell design</li> <li>Twin compartment (gasoline/diesel)</li> <li>Integrated pumping up to 150 l/min</li> <li>Cold climate specification</li> <li>Ballistic protection to STANAG 4569 Level 3</li> <li>Genset for autarkic operation</li> <li>Telematics</li> <li>Wide range of dispensing options</li> </ul>

Issue 1/2017. Basic specifications subject to change without prior notice.

