



LIGHT VEHICLE MODULE - WATER

FORWARD AREA/MRAP-CAPABLE PLATOON-LEVEL WATER SUPPLY. DELIVERS UP TO 6,000L OF DRINKING AND NON-POTABLE WATER.



Demountable water delivery and dispensing system with integrated pumping system.

Transportable by MRAP utility vehicles, 4X4 and 6X6 logistics vehicles.

Compatible with on-board vehicle crane or forklift handling systems.

Very low profile system for forward-area or command-level water supply.

[HIGHLY CUSTOMIZABLE TO MEET YOUR REQUIREMENTS](#)

NATO Stock Number: 2330-01-580-7654

INTERMODAL



BASE SPECIFICATION

Length	2,991 - 4,570 mm / 10' - 15'
Width	2,438 mm / 8'
Height	1,220 - 1,727 mm / 4'0" - 5'8"
Payload range	2,000 - 6,000 litres / 525 - 1,575 U.S. gallon
Tare range (typical)	975 - 2,000 kg / 2,145 - 4,400 lbs
Max. gross range	3,000 - 8,000 kg / 4,400 - 22,000 lbs
Stacking	192,000 kg / 423,320 lbs
Build codes	AD-Merkblätter, BetrSichV
Transport codes (Road, Rail, Sea)	RID, Customs (for ISO modules), Lloyd's Register, BAM, ISO 1496/3, UIC 592-2 (as far as applicable), CSC, ISO 3874
Materials	1.4404 (316L) stainless steel.
Working pressure	+0.1 - 2.6 bar / +1.5 - 37.5 psi
Temperature range (inner)	-40 - + 50 °C / -40 - + 122 °F
Optional equipment	<ul style="list-style-type: none"> Genset compartment Powered pumping (in/out) Onboard water heaters/chillers Clean-in-place tank Onternal cleaning Compact reverse osmosis/ultra-filtration Insulation/antifreeze protection

Issue 1/2017. Basic specifications subject to change without prior notice.

