



# MAIN CAMP AND BASE - FUEL

**MULTI FUEL: STORES UP TO 51,000L OF DIESEL,  
GASOLINE, A-1 JET FUEL.**



Military forward operating base, main base and airfield infrastructure fuel storage and dispensing systems.

Each tank fitted within a standard ISO frame, which can be coupled together for scalable solution.

Single or EPA-approved double-shelled tanks with leakage indicator

Transportable by road, rail and maritime networks

[HIGHLY CUSTOMIZABLE TO MEET YOUR REQUIREMENTS](#)

NATO Stock Number: 8145-12-367-6165

## INTERMODAL



## BASE SPECIFICATION

<b>Length</b>	6,058 - 12,192 mm / 20' - 40'
<b>Width</b>	2,438 mm / 8'
<b>Height</b>	1,220 - 2,591 mm / 8' - 8'6"
<b>Payload range</b>	3,000 - 51,000 litres / 1,575 - 13,420 U.S. gallon
<b>Tare range (typical)</b>	2,000 - 8,800 kg / 4,400 - 19,360 lbs
<b>Max. gross range</b>	5,000 - 60,000 kg / 67,200 - 79,370 lbs
<b>Stacking</b>	192,000 kg / 423,320 lbs
<b>Build codes</b>	AD-Merkblätter, WHG, VAWS, BetrSichV
<b>Transport codes (Road, Rail, Sea)</b>	ADR, RID, IMDG (T2-T10), IATA, Customs, Lloyd's Register, BAM, ISO 1496/3, UIC 592-2 (as far as applicable), CSC, ISO 3874
<b>Materials</b>	Carbon steel, 1.4301/1.4404 stainless steel. Double-shell design with leakage indicator.
<b>Working pressure</b>	2.0 - 4.0 bar / 30 - 60 psi
<b>Temperature range (inner)</b>	-40 - + 50 °C / -40 - + 122 °F
<b>Optional equipment</b>	<ul style="list-style-type: none"> <li>Single/double-shell design</li> <li>Twin compartment (gasoline/diesel)</li> <li>Integrated pumping up to 1,500 l/min</li> <li>Rotary and fixed-wing refueller options</li> <li>Cold climate specification (heater)</li> <li>Manifold option. Up to 5 separate supplies via dry-break connectors</li> <li>Telematics</li> </ul>

Issue 1/2017. Basic specifications subject to change without prior notice.

