



# MAIN CAMP AND BASE - WATER

STORES AND DISPENSES UP TO 20,000L OF  
POTABLE WATER.



Field camps, hospitals, kitchens, ablution facilities.

Each tank fitted within a standard 20' ISO dimensions, which can be coupled together for scalable solution.

ICAO/IATA Option

Transportable by road, rail and maritime networks.

[HIGHLY CUSTOMIZABLE TO MEET YOUR REQUIREMENTS](#)

NATO Stock Number: 8145-12-346-8311

## INTERMODAL



## BASE SPECIFICATION

<b>Length</b>	6,058 - 12,192 mm / 20' - 40'
<b>Width</b>	2,438 mm / 8'
<b>Height (nominal)</b>	2,438 - 2,591 mm / 8' - 8'6"
<b>Payload (nominal)</b>	18,000 litres / 4,755 U.S. gallon
<b>Tare range (nominal)</b>	4,800 kg / 10,582 lbs
<b>Max. gross range</b>	30,480 - 36,000 kg / 67,200 - 79,370 lbs
<b>Stacking</b>	192,000 kg / 423,320 lbs
<b>Build codes</b>	AD-Merkblätter, WHG, VAwS, BetrSichV, TÜV (control box), DEKRA
<b>Transport codes (Road, Rail, Sea)</b>	Customs, Lloyd's Register, BAM, ISO 1496/3, UIC 592-2 (as far as applicable), CSC, ISO 3874, IATA
<b>Materials</b>	1.4404 stainless steel.
<b>Working pressure</b>	+0.1 - 2.6 bar / +1.5 - 37.5 psi
<b>Temperature range (inner)</b>	-40 -+ 50 °C / -40 -+ 122 °F
<b>Optional equipment</b>	<ul style="list-style-type: none"> <li>Powered pumping (in/out)</li> <li>High capacity loading/discharge pump</li> <li>Clean-in-Place tank cleaning</li> <li>Reverse osmosis/ultra-filtration</li> <li>Automatic chlorine dosing/ UV-radiation</li> <li>Firefighting pump</li> <li>Powered by heavy-duty generator set or external power</li> <li>Water heaters/ chillers</li> <li>Telemetry options</li> </ul>

Issue 1/2017. Basic specifications subject to change without prior notice.

