



The Fully-Featured RANGERX

The Lightest, Most Rugged Tablet In Its Class





The RangerX's many integrated features make it the most capable lightweight rugged tablet in the industry.

BUILT RUGGED TO WITHSTAND YOUR WORKLOAD

- Lightweight Platform For Ultra Mobility
- O Full Shift Battery Life Up To 10 Hours
- O MIL STD 810G Certified From The Experts In Rugged
- O IP65 Rated For Protection From Dust And Liquids
- O Brilliant Outdoor Viewable Multi-Touch Display
- O Largest Storage Capacity In Class (192GB)
- O HD Front and 5MP Rear Camera
- O Android[™] 4.2.2 Operating System with Google Play
- O Over-the-Air Updating Enabled by Red Bend Software
- Comprehensive Communications Suite
- Glove Touch Capable for Hazardous Industries
- Optimizied for Carriers
 - Gigabit Ethernet For Blazing Connectivity (Optional)
 - HDMI-In (Optional)
- Integrated Common Access Card Reader (Optional)

FULLY RUGGED & LIGHTWEIGHT

Inspired by over a decade of customer feedback and experience in the rugged tablet space, the RangerX features a lightweight and highly portable form factor, without compromising the ultra-rugged, reliable protection of the Xplore iX104 line. With MIL-STD-810G and IP65 certifications, the RangerX is engineered to protect critical data under the most challenging conditions, with a weight profile that accommodates the mobile professional.

FULLY FEATURED AND POWERFUL

Powered by a modern dual core ARM Cortex A9 processor and the largest storage capacity in its class, the RangerX offers a full suite of enterprise tools for any application. Front and rear cameras, an integrated CAC option, a vast array of I/O, and optional HDMI-In and Gigabit Ethernet ports give the RangerX the flexibility to run your most demanding projects. A multi-modal communications suite including 4G LTE enables realtime data transfer and uninterrupted communications for your field workers.

FOR THE MOBILE PROFESSIONAL

The RangerX sets the standard for field mobility: a full shift battery life, lasting up to ten hours, maximizes time in the field and boosts productivity. The RangerX's brilliant outdoor viewable, multi-touch display allows seamless transition from indoor to outdoor use. Options for carrying straps, handles, and mobile docking makes tablet transportation easy for handheld and vehicle applications.

TOTAL CONTROL OF OWNERSHIP

The RangerX incorporates many of the design elements of Xplore's flagship product and is designed to provide a long service life in the field. And with an integrated, over-the-air updating capability enabled by Red Bend Software, the RangerX is guaranteed to always be upto-date. Xplore has a proven track record in providing reliable products with long, stable life cycles that keep workers productive and contribute to lower total cost of ownership.

CIOSCOD



GRAPHICS

INTEGRATED

SECURITY

facing)



FULLY RUGGED Magnesium Alloy Midframe **PORTS** AC/DC power

Integrated POWERVR™ SGX544 graphics accelerator

2 USB 2.0 Ports (Full and Micro) MIL-STD-810G and IP65 Tested

Elastomer Bumpers (Protected Glass/Touch Screen) Micro SD Multiple 4' drops, (26, Single Operating Unit) Micro HDMI-out SIM Card Reader

PROCESSOR Dual Core ARM Cortex A9 Processor Smart Card Reader (CAC Reader, Optional)

L2 Smart Cache: 1MB RJ-45 / mini HDMI-in Module (Optional) 1.5GHz Headphone/Speakers and Mic

Speaker

Integrated Image Signal Processor **INPUT AND Projected Capacitance Multitouch**

STATUS Glove Touch Capability Available for Download at **DISPLAY** 10.1" WXGA (1366 x 768) Rugged IPS LCD Backlit Display **INDICATORS** http://www.xploretech.com/download-center

500 NITS Direct Bonded Screen STATUS INDICATORS: Power, Charge/DC-in 178° Viewing Cone (89° Off-Axis)

Contrast Ratio = 800:1; Aspect Ratio: 16:9 **DIMENSIONS /** 11.1" (28.2 cm) x 7.2" (18.3 cm) x 0.85" (2.15 cm) (W x H Automatic Light Sensor (ALS) WEIGHT xD)

Multi-Touch, Anti-Reflective Glass Starting at 2.2 lbs (0.99 kgs)

MEMORY Dual-channel LPDDR2 memory **PERIPHERALS** Vehicle Dock 1 GB

AND DOCKING

OPERATING Android [™] 4.2.2 (Jelly Bean) **ENVIRONMENTAL** Independently-tested to MIL-STD-810G **SYSTEMS** Over-the-air Updating Service Enabled by Red Bend **SPECIFICATIONS**

OPERATING TEMPERATURE: -20° C to +60° C / -4° F to Software

STORAGE TEMPERATURE: -20° C to 70 °C / -4° F to 158 °F **BATTERY** User Replaceable 10,000 mAhr HUMIDITY: 95% non-condensing

Up to 10 hour battery life VIBRATION: Minimum Integrity, Vehicle Vibration, US

Highway Truck Vibration

POWER SUPPLY Auto-sensing 100-240 V, 50-60 Hz supplying 12 VDC, ALTITUDE: 15,000 ft (4,572 m) operating

OTHER TESTS: Functional (20G Operating, 40G Non

USB Charging Supported Operating) and Crash Shock

TRANSIT DROP - OPERATING: 4' (1.22 m) drop direct to STORAGE OPTIONS 32G eMMC NAND Flash Memory plywood over concrete while system is operating, 26

Additional Secured Internal Micro SD up to 128GB drops

(Optional)

User Accessible 32G micro SD **IEC INGRESS** IEC (60529) Ingress Tested to an IP65 standard **TESTING**

WIRELESS LAN: 802.11 a/b/g/n **COMMUNICATIONS** BROADBAND: 4G LTE (Optional) **EMISSIONS &** IMMUNITY: CISPR 24, EN 55024 CB Scheme (US, CAN,

GPS: Integrated, 5m accurate satellite **IMMUNITY** FU27) BLUETOOTH: 4.0 EMISSIONS: CB Scheme EN 55022, CISPR 22 CFR 47 Part

FM Transmitter

15, subpart B, ICES-003 for class B (US, CAN, EU27), IEC LAN: 10/100/1000 Gigabit Ethernet (RJ-45) (Optional) 60950 CB Scheme (US, CAN, EU27)

Integrated Smart Card Reader with CAC capability (Optional) **ENVIRONMENT** ROHS, Energy Star 5.0 Compliant, EPEAT

Kensington lock slot RECYCLING PROGRAM:

www.xploretech.com/environment/recycle

COLLABORATION NFC RFID

> Integrated speaker WARRANTY Standard 3 Year Limited Warranty Microphone Extended Warranty & xDefend Programs available.

Integrated 5 Megapixel digital camera (rear-facing w/ Please contact Sales or visit http://www.xploretech.

ACCESSORIES

Handle/Shoulder Strap

xDock G2 Automotive Docking Solution

com/warranty for further information. Integrated HD Megapixel digital camera (forward-

Back Handstrap Stylus

Armortech Screen Protector