





AMMUNITION

- TP & TP-T
- HE & HE-T
- HEI & HEI-T
- AP & AP-T
- API & API-T

Target practice (+ Tracer) High explosive (+ Tracer) High explosive incendiary (+ Tracer) Armour piercing (+ Tracer) Armour piercing incendiary (+ Tracer)

HS804

20 x 110 mm

620 - 780 rpm

835 m/s (2,740 ft/s)

5,700 m (6,234 yds)

2,000 m (2,187 yds)

4.5 kN (1,012 lbf)

1.6 kN (360 lbf)

42.8 kgf (94.4 lbf)

5.6 kgf (12.3 lbf)

CANNON SPECIFICATION

- Cannon Type
- Calibre:
- Rate of fire:
- Muzzle velocity:
- Range (max):
- Range (effective)
- Recoil force (max):
- Recoil force (mean):
- Weight of cannon (less magazine):
- Weight of belt feed Drum magazine:





AE20 - VM2

DESCRIPTION

The AE20-VM2 is a lightweight all Aluminium vehicle weapon mount for the HS804 20 mm gun. The mount accepts AEI's drum type belt feed mechanism for prolonged target engagements. The mount also accepts AEI's lower profile 'flat' belt feed mechanism and can simply revert to accept AEI's linkless feed drum magazine associated with the AE20-NM naval mount.

The cradle is sprung loaded to assist the operator engage elevated targets and balance the gun horizontally whilst vehicle trundling. The weapon mount can be readily fitted to a vehicle slewing ring, roof, bulkhead or pedestal.

The ammunition feed tank elevates with the gun cradle to ensure smooth ammunition feed.

THE MOUNT

- Traverse arc:
- Elevation arc:
- Swept radius:
- Height:
- Weight (Less gun & ammunition):

360° with optional adjustable safety arc stops -15° to +58° 1.68 m (66 in) at 0° elevation 540 mm; base to barrel centreline 75 kgf (165 lbf)





AEI Systems Ltd

1 Kings Ride Park, Ascot, Berkshire. SL5 8AP United Kingdom

