

Model - 4120

5kW Auxiliary Power Unit 230 VAC, 28 Volts D/C, 50Hz

APU FEATURES

Permanent Magnet Alternator
High Efficiency DC Regulator
Remote Control ability
Welded steel frame to provide rigid support
Four access panels for off service and maintenance

General Specification

Dimensions/Dry Weight: 490 lbs (222Kg), 39" x 36" x 24" (990mm x 914mm x 609mm)
Noise: <74dBA @ 7 meters

Power Supply

Farymann 43F Diesel, 15HP, Air Cooled, 24V electric and manual start
Fuel Consumption: 8 liters per hour at full load
Servicing Frequency: 50 hours
Oil Capacity: 4.26 liters

Output

230 volts AC, 50Hz, wave form distortion less than 2.5%
28 volt DC voltage variation, ripple less than 3%



Headquarters
Goodman Ball, Inc.
3639 Haven Ave
Menlo Park, CA 94025
Phone: 877/424-4797
Fax: 650/363-8294
E-mail: sales@goodman.com

European Office
C. E. Niehoff & Co. Ltd.
No. 7 Peregrine Place, Moss Side, Leyland,
Preston, PR25 3EY, United Kingdom
Phone: 44/1772-459777
Fax: 44/1772-624666
Email: info@niehoff.co.uk