

TCS Space & Component Technology

IDE BGADrive® - Solid State Drive



Features

- Available now in 16GB and 32GB
- ATA-6 standard compatible in True-IDE Mode
- Fast ATA transfer rates supporting PIO mode 6, MDMA mode 4, UDMA mode 4 in True-IDE Mode
- JEDEC standard 22 x 22 BGA with 1.27mm pitch
- Operates with either +3.3 or +5 VDC $\pm 10\%$
- Automatic power-down and sleep modes
- Industrial grade SLC NAND Flash
- High-reliability eutectic Sn-Pb BGA solder balls
- Meets Mil-Std-810 shock and vibration requirements
- Integrated ECC and CRC detect and correct up to 4 random bytes per 512-byte sector
- No device driver development required (completely compatible with standard ATA drivers)

TCS Space & Component Technology now offers IDE BGADrive®, a Solid State Drive (SSD) in an ultra-rugged ball-grid-array package of only 31mm x 31mm. A standard IDE / PATA interface allows ease of software integration — for many operating systems, no driver development is required.

The controller architecture is based on a 32-bit RISC processor and connects directly to two, four or eight NAND flash memory devices (2 per channel). A powerful direct flash access (DFA) mechanism handles the data transfer tasks, including the two flash memory concurrent-access channels. Acting independently as a hardware accelerator, the DFA mechanism provides a significant performance advantage.

An on-chip ECC and CRC unit generates the required code bytes for error detection and correction of up to four random bytes per 512 Byte data sector. Code byte generation during write operations, as well as error detection during read operation, is implemented on the fly without any speed penalty. An advanced static wear-leveling algorithm not only maximizes the usable life of the media, but also incorporates software routines which optimize the spread of cells addressed to reduce chances of data errors arising from parasitic coupling or floating-gate-to-floating-gate noise.

The BGADrive® supports mobile applications with automatic power-saving states, and power-fail management. Designed and manufactured in the USA at AS9100-certified facilities, the Trident's SSDs are the unquestioned reliability leaders among high-performance, rugged SSDs.

Applications

- Single-board computers in military settings
- Ruggedized computers / notebooks — mobile and system-based
- Data recorders for extreme environments
- Ultra-portable and hand-held devices
- Ruggedized PDAs, military logistics
- Security / surveillance networks / image processing
- Wearable computers
- UAVs, UAVs
- Defense / Aerospace
- Miniature network appliances
- Embedded / Industrial
- Medical instrumentation
- Transportation equipment
- Outdoor / Mobile applications for telecoms, IT systems, utilities

Contact

TCS Space & Component Technology

USA Office

19951 Mariner Avenue, Building 157

Torrance, CA 90503 USA

Tel: 866.264.0793

Email: sctsales@telecomsys.com

European Office

PO Box 686

Fareham PO14 9 NR

United Kingdom

Tel: +44 (0) 75904 63366

Email: sctsales@telecomsys.com

See TCS' complete line of products and services at www.telecomsys.com.

Your Established Partner

TCS brings proven, technology problem-solving expertise to its professional service offerings for the public sector. From continuity of operations and information assurance, to cyber security and integrated logistics support, TCS solves the toughest technical challenges, under conditions that demand the highest level of reliability, availability, and security. As an ISO 9000-certified provider with many consultants holding active security clearances, TCS has an established track record over the past decade as a trusted partner providing mission continuity for the Department of Defense, Special Operations and intelligence communities, the Department of Homeland Security, and the Department of State.

TeleCommunication Systems, Inc.

275 West Street

Annapolis, MD 21401 USA

Toll Free: 1.888.728.8797

Outside US: +1.410.263.7616

www.telecomsys.com

Enabling Convergent Technologies® is a registered trademark of TCS. All other trademarks are the property of their respective companies. Information subject to change without notice. | NasdaqGM: TSYS | 080112

Specifications

Performance

Capacity	16GB, 32GB
Sustained Read (32GB)	Up to 42 MB/s
Sustained Write (32GB)	Up to 27 MB/s
Random Read, 1MB blocks (32GB)	Up to 40 MB/s
Random Write, 1MB blocks (32GB)	Up to 14 MB/s

Power

Input Voltage	+5VDC \pm 10% or +3.3VDC \pm 10%
Read Max (32GB)	0.85 W at +5VDC
Write Max (32GB)	0.90 W at +5VDC
Standby Power (32GB)	<0.05 W at +5VDC

Reliability


Bit Error Rate	< 1 non-recoverable error in 10^{14} bits read
Error Detection / Correction	Up to 4 random byte errors detected and corrected in 512 byte sector
Data Retention	> 10 years
Endurance	> 100,000 writes
Wear-Leveling	Proprietary algorithms

Environment

Operating Temperature	-40°C to +85°C
Storage Temperature	-50°C to +95°C
Temperature Cycle	JEDEC JSDSTD22-A104 (-40°C to +85°C); 200 cycles minimum
Temperature Humidity Bias (THB)	JEDEC JESD22-101 (85°C / 85%RH) for 1,000 hours
Altitude	> 80,000 feet
Humidity	5% to 95% relative humidity, non-condensing
Shock	1,500G at 0.5ms
Vibration	16.3G minimum RMS

Mechanical

Dimensions (mm)	JEDEC Standard BGA (31mm x 31mm with 22 x 22 ball array and pitch = 1.27mm)
-----------------	---



Product Information and Specifications subject to change without notice. DS-TSDXBGP-A