



PACHR3600

Portable, Powerful, Practical

Port-A-Cool® Unit Specifications

- Energy efficient • Cools up to 4,000 sq. ft., depending on model • Lowers temperature as much as 30 degrees F



Part Numbers*	Descriptions	Cooling Capacity (square feet)	CFM	TOTAL AMPS	WATER (gallons)	Weight (lbs)	Dimensions H X W X D
PREMIUM SERIES							
PACHR3600	Hurricane 3600	3,500	14,500	11.4	67	270	76.5 x 74.5 x 35
PACJS2400	JetStream® 2400	2,000	7,500	9.2	48	200	72 x 54.5 x 28
PACJS1600	JetStream® 1600	1,000	4,000	5.3	42	109	59 x 37 x 24.5
PRO SERIES							
PAC2K482S	48" Two-Speed	4,000	20,000	12.0	40	345	86 x 74 x 36
PAC2K36HPVS	36" HP Variable Speed	2,650	10,100	11.0	32	200	67 x 62 x 32
PAC2K363S	36" Three-Speed	2,500	9,600	11.2	32	205	67 x 62 x 32
PAC2K24HPVS	24" HP Variable Speed	1,800	6,700	8.8	14	155	53 x 50 x 25
PAC163SVT	16" Vertical Tank	900	3,900	5.1	42	130	59 x 37.5 x 23
CLASSIC SERIES							
PAC2K361S	36" Single-Speed	2,500	9,600	10.8	32	195	67 x 62 x 32
CYCLONE SERIES							
PAC2KCYC01	Cyclone® 3000 Black	700	3,000	5.6	16	100	38 x 29 x 25
PACCYC02	Cyclone® 2000 Black	500	2,000	2.5	10	61	31 x 24 x 25
SPECIAL APPLICATION							
PAC2K36HZ	36" Hazardous Location	2,500	9,600	13.4	N/A	300	67 x 62 x 32
PAC2K48HZ	48" Hazardous Location	4,000	20,000	18.0	N/A	400	86 x 74 x 36

For more information, call 1-800-695-2942 or (936) 598-5651 or visit us online at
www.port-a-cool.com • www.kuulpads.com



Port-A-Cool® units and KÜÜL® pads evaporative cooling media are manufactured by Port-A-Cool, LLC • Center, Texas 75935 • Member of the Walter Meier Group

