

## PROTECTOR M21 4x4 Modular Armoured Vehicle (MAV)

- Commercially available components
- Multi-role capability
- Low maintenance cost



Website:www.ott.co.za Email: armour@ott.co.za

## **BASIC SPECIFICATIONS**

## M21 4x4 MODULAR ARMOURED VEHICLE (MAV)

Specifications are subject to change without prior notice

**ENGINE** 

Type Hino 4 Stroke Diesel (Euro 2 emission)

Configuration In line 6 Cylinder

Displacement 7684 cc

Max Power 152 kW @ 2 500 rpm Max Torque 603 Nm @ 1 500 rpm

Fuel Type Diesel

TRANSMISSION &TRANSFER CASE

Type Hino LX 06 S 6 speed synchromesh

Transfer case Hino 2-speed 4x4 selectable

STEERING

Type Power assisted re-circulating ball

Steering wheel orientation Right Hand Drive

**BRAKES** 

Service brakes Air over hydraulic

ABS No

Parking brake Spring brake on rear

SUSPENSION

Type Semi elliptic leaf springs

Shock absorbers Double acting telescopic hydraulic

WHEELS AND TYRES

Rim &Tyres size Rim size: 7.00 x 20 Tyre size: 10.00 R20

Run Flat Inserts Optional

CONFIGURATION

Seating APC: Driver, commander plus up to 10

CIT: driver, commander plus up to 4

Models APC, CIT, Incident command

STANDARD FITMENT

Air conditioner High capacity

Defence ports Front, sides and rear of vehicle

Seat belts Fitted to all seats

ELECTRICAL SYSTEM 24 Volt

**DIMENSIONS** 

Overall length 7 200 mm
Body width 2 400 mm
Overall height 2 800 mm
Ground clearance (min) 280 mm
Fuel capacity 200 litre

**VEHICLE MASS** 

Tare 9 000 kg
Gross vehicle mass (GVM) 13 000 kg
Payload 4 000 kg

**PERFORMANCE** 

Max speed 100 km/h Sustained road speed 90 km/h

Fuel autonomy > 500 km with full load on roads

**PROTECTION** 

The monocoque hull protects the crew and engine against rifle fire

and hand grenates

Errors and omissions excluded

