


CRÈDO CUBE™ SERIES 20M PRODUCT SPECIFICATION

CRÈDO™ SERIES 20M -25°C TO -15°C

Payload Size	Exterior Dimensions - mm	Interior Dimensions - mm	Insulation	Outer Material	Tare Weight - kg
3L	318 x 267 x 279	130 x 130 x 130	Single Wall VIP	White Plastic	7
4L	318 x 267 x 279	150 x 150 x 150	Single Wall VIP	White Plastic	6
4L	381 x 343 x 349	150 x 150 x 150	Nested VIP	White Plastic	10
8L	445 x 286 x 292	282 x 165 x 165	Single Wall VIP	White Plastic	9
10L	381 x 343 x 349	216 x 216 x 216	Single Wall VIP	White Plastic	14
12L	381 x 343 x 349	226 x 226 x 226	Single Wall VIP	White Plastic	12
12L	457 x 419 x 432	226 x 226 x 226	Nested VIP	White Plastic	19
16L	419 x 375 x 381	254 x 254 x 254	Single Wall VIP	White Plastic	14
16L	464 x 432 x 445	254 x 254 x 254	Nested VIP	White Plastic	20
28L	457 x 419 x 432	305 x 305 x 305	Single Wall VIP	White Plastic	20
28L	540 x 495 x 502	305 x 305 x 305	Nested VIP	Kraft Box	30
56L	540 x 495 x 502	381 x 381 x 381	Single Wall VIP	Kraft Box	30
56L	673 x 673 x 641	381 x 381 x 381	Nested VIP	Duracube HD	53
96L	673 x 673 x 641	457 x 457 x 457	Single Wall VIP	Duracube HD	54

Internal / external dimensions may vary subject to approved tolerances.

Series 20M 2896 ISTA Summer Thermal Performance




CRÈDO CUBE™ SERIES 50M (-40°C AND COOLER) PRODUCT SPECIFICATION

Payload Size	Exterior Dimensions - mm	Interior Dimensions - mm	Insulation	Outer Material	Tare Weight - kg
4L	381 x 343 x 349	150 x 150 x 150	Nested VIP	White Plastic	10
12L	457 x 419 x 432	226 x 226 x 226	Nested VIP	White Plastic	19
16L	464 x 432 x 445	254 x 254 x 254	Nested VIP	White Plastic	20
28L	540 x 495 x 502	305 x 305 x 305	Nested VIP	Kraft Box	30
56L	673 x 673 x 641	381 x 381 x 381	Nested VIP	Duracube HD	54
96L	673 x 673 x 641	457 x 457 x 457	Single Wall VIP	Duracube HD	56

Internal / external dimensions may vary subject to approved tolerances.

Series 50M - 2896, ISTA Summer Thermal Performance



Superior Performance
ensuring complete
product integrity

Small and Light
significantly reducing
distribution costs

**Crêdo ProEnvision™ and
Service Centers**
support reclamation
and re-use

FOR MORE INFORMATION ABOUT PELI BIOTHERMAL PRODUCTS, PLEASE CONTACT:
INFO@PELIBIOTHERMAL.COM T: +44 (0)1525 243 770 PELIBIOTHERMAL.COM

ISO17025, ISO9001-2008 Accredited

Golden Hour™, TIC™, Crêdo™, Crêdo Cube™, Crêdo ProEnvision™, Crêdo Xtreme™, Crêdo DURACUBE™, Crêdo ProMed™, Sherpa™ Systems, CoolGuard™ PCM, CoolGuard™ Advance, CoolPall™ Flex and CoolPall™ Vertos are registered trademarks of Pelican Products, Inc., its subsidiaries and/or affiliates.



©2019 PELI BioThermal all rights reserved.



CRÈDO CUBE™ SERIES 4, 22, 20M & 50M

Superior thermal protection in a convenient mid-size container.

The Crêdo Cube™ is a passive and reusable shipper qualified to hold chilled medical materials at a safe temperature for up to five days. This system is ideal for reducing shipping costs or for circumstances in which unexpected delays may occur.

Modular TIC™ (Thermal Isolation Chamber) walls with integrated PCM (Phase-Change Material) and VIPs (Vacuum Insulated Panels) makes conditioning in a freezer for year-round shipping easy and allows effortless packing and storage.

WHY CHOOSE CRÈDO™ SYSTEMS?

- The most trusted and reliable brand of high-performance reusable shippers with the largest number of sizes and temperature ranges available
- TIC™ walls contain PCM and completely enclose the temperature-sensitive payload ensuring consistently stable performance
- Crêdo™ shippers are highly durable, lightweight, and provide an optimum volume ratio of interior payload space for your products - allowing you to ship more product in fewer containers, reducing distribution costs



ENHANCE YOUR CRÈDO™ SYSTEMS

- Crêdo ProEnvision™:** Easy-to-use, secure, web-based asset tracking software and global service centers available to assist customers and maximise their return on investment
- TIC™ Smart Indicator:** Optional temperature-sensitive label installation specifying an "at a glance" safe temperature reading

CRÈDO CUBE™

DURATION
96 - 168 Hours

SERIES 4
(2°C to 8°C)

VOLUME
3L, 4L, 8L, 10L, 12L, 16L,
28L, 42L, 56L, 96L

SERIES 22 CONTROLLED
(15°C to 25°C)

VOLUME
3L, 4L, 8L, 10L, 12L, 16L,
28L, 42L, 56L, 96L

SERIES 22 UNIVERSAL
(15°C to 25°C)

VOLUME
9L, 24L, 49L

SERIES 20M
(-25°C to -15°C)

VOLUME
3L, 4L, 8L, 10L, 12L, 16L,
28L, 56L, 96L

SERIES 50M
(-40°C and Cooler)


VOLUME
4L, 12L, 16L, 28L,
56L, 96L

CRÈDO CUBE™ SERIES 4 PRODUCT SPECIFICATION

Payload Size	Exterior Dimensions - mm	Interior Dimensions - mm	Insulation	Outer Material	Tare Weight - kg
3L	318 x 267 x 279	130 x 130 x 130	Single Wall VIP	White Plastic	6
4L	318 x 267 x 279	150 x 150 x 150	Single Wall VIP	White Plastic	5
4L	381 x 343 x 349	150 x 150 x 150	Nested VIP	White Plastic	9
8L	445 x 286 x 292	282 x 165 x 165	Single Wall VIP	White Plastic	8
10L	381 x 343 x 349	216 x 216 x 216	Single Wall VIP	White Plastic	11
12L	381 x 343 x 349	226 x 226 x 226	Single Wall VIP	White Plastic	10
12L	457 x 419 x 432	226 x 226 x 226	Nested VIP	White Plastic	16
16L	419 x 375 x 381	254 x 254 x 254	Single Wall VIP	White Plastic	11
16L	464 x 432 x 445	254 x 254 x 254	Nested VIP	White Plastic	17
28L	457 x 419 x 432	305 x 305 x 305	Single Wall VIP	White Plastic	16
28L	540 x 495 x 502	305 x 305 x 305	Nested VIP	Kraft Box	25
42L	616 x 419 x 432	457 x 305 x 305	Single Wall VIP	White Plastic	21
56L	540 x 495 x 502	381 x 381 x 381	Single Wall VIP	Kraft Box	25
96L	673 x 673 x 641	457 x 457 x 457	Single Wall VIP	Duracube HD	46

Internal / external dimensions may vary subject to approved tolerances.

Series 4 - 2896, Unit 3 ISTA Summer Thermal Performance



CRÈDO CUBE™ SERIES 22 CONTROLLED PRODUCT SPECIFICATION

Controlled


Our standard Series 22 product designed for trips in controlled shipping lanes with a reliable certainty of external temperature during transit.

CRÈDO™ SERIES 22 CONTROLLED 15°C TO 25°C

Payload Size	Exterior Dimensions - mm	Interior Dimensions - mm	Insulation	Outer Material	Tare Weight - kg
3L	318 x 267 x 279	130 x 130 x 130	Single Wall VIP	White Plastic	6
4L	318 x 267 x 279	150 x 150 x 150	Single Wall VIP	White Plastic	5
4L	381 x 343 x 349	150 x 150 x 150	Nested VIP	White Plastic	9
8L	445 x 286 x 292	282 x 165 x 165	Single Wall VIP	White Plastic	8
10L	381 x 343 x 349	216 x 216 x 216	Single Wall VIP	White Plastic	11
12L	381 x 343 x 349	226 x 226 x 226	Single Wall VIP	White Plastic	10
12L	457 x 419 x 432	226 x 226 x 226	Nested VIP	White Plastic	16
16L	419 x 375 x 381	254 x 254 x 254	Single Wall VIP	White Plastic	11
16L	464 x 432 x 445	254 x 254 x 254	Double Wall VIP	White Plastic	17
28L	457 x 419 x 432	305 x 305 x 305	Single Wall VIP	White Plastic	16
28L	540 x 495 x 502	305 x 305 x 305	Nested VIP	Kraft Box	25
42L	616 x 419 x 432	457 x 305 x 305	Single Wall VIP	White Plastic	21
56L	540 x 495 x 502	381 x 381 x 381	Single Wall VIP	Kraft Box	24
96L	673 x 673 x 641	457 x 457 x 457	Single Wall VIP	Duracube HD	46

Internal / external dimensions may vary subject to approved tolerances.

Series 22 Controlled - 2896 ISTA Summer Thermal Performance



CRÈDO CUBE™ SERIES 22 UNIVERSAL PRODUCT SPECIFICATION

Universal

Series 22 Universal has been specially designed for more challenging shipping lanes, which could feature a wide variance of temperature during the trip duration.

CRÈDO™ SERIES 22 UNIVERSAL 15°C TO 25°C

Payload Size	Exterior Dimensions - mm	Interior Dimensions - mm	Insulation	Outer Material	Tare Weight - kg
9L	381 x 343 x 349	206 x 206 x 206	Single Wall VIP	White Plastic	11
24L	457 x 419 x 432	291 x 291 x 291	Single Wall VIP	White Plastic	19
49L	540 x 495 x 502	366 x 366 x 366	Single Wall VIP	White Plastic	27

Internal / external dimensions may vary subject to approved tolerances.



Series 22 Universal - 9L, Unit 3, ISTA Summer Thermal Performance

