

Guardian Trident Survival Water Sensing Life Jacket Beacon



PRODUCT NUMBER:

58700-OY-F-WP-4-WTIR-R-RP-FP-MSCY

MANUAL SAFETY CLIP (INCLUDED)

P/N: 49055-YL



Locks switch ring bezel in place, intended to prevent accidental function change when set to AUTOMATIC Water Activation

Candela vs. Angle



BATTERY DURATION

Function Duration

60 BPM Flash Min. 25 Hours

*Tested at -5°C Duration may vary with temperature.


TECHNICAL SPECIFICATIONS

BATTERY SOURCE
HOUSING MATERIAL
HOUSING COLOR
DOME LENS
OPERATING TEMPERATURE
STORAGE TEMPERATURE
WATERPROOF RATING
WHITE LIGHT OUTPUT

One (1) Lithium 3Vdc (Type: 123A)
HIGH-TECH POLYMER
ORANGE / YELLOW
HIGH IMPACT POLYCARBONATE
-20 to +60°C / -4 to +140°F
-20 to +60°C / -4 to +140°F
330Ft (100 Meters)
2000Ft. Altitude @ 3 Nautical Miles
Min. 1 Candela, Over An Entire Half

Hemisphere (180° x 360°)

LIGHT FUNCTIONS



*To avoid unintentional deactivation in turbulent water conditions, this position features a 20 second deactivation delay when sensory probe is removed from the water.

Please note: All MANUAL functions, including the OFF Position on the Bezel, will be overridden by 60 BPM Flashing when probe is immersed in water. However, unlike the AUTOMATIC Water Activated Position, this signal will deactivate immediately once removed from water and the light will return to the selected position's original function.



Specifications subject to change without prior notice DOC. ID: P-PS-58700-OY-F-WP-4-WTIR-R-RP-FP-MSCYr8 Jan 2020




Guardian Trident Survival Water Sensing Life Jacket Beacon

The Guardian[™] Trident Survival Light is an ideal personal safety and tactical light, with the option of water activation to enhance soldier safety during training and operations. This lightweight, robust and durable product is half the weight of our legendary VIP[™] light, but maintains many of the robust characteristics our flagship product is known for.

FEATURES

- One-handed operable
- Compatible with both Hook/Loop and 3M Dual Lock™ Fasteners
- Rounded shape to help prevent snag hazard
- Rugged body, waterproof up to 330 feet (100 meters) and extremely resistant to impact
- Failsafe system separates Overt and Covert modes by Reverse Polarity Program Switching®; to prevent accidental overt activation.
- Positive feedback switch ring with raised switch position nub for easy tactile feedback.
- Automatically locks in ring position. Depress with two or more fingers to turn
- Unique water-activated sensor is mist, fog and splash resistant. Must be immersed in water to activate.
- US Coast Guard, Transport Canada & SOLAS Compliant.
- Fully assembled light with pad will float.
- Unique Removable Manual Safety Clip will prevent the bezel from moving accidentally during either compressed installation or inadvertent contact



Specifications subject to change without prior notice

DOC. ID: P-PS-58700-OY-F-WP-4-WTIR-R-RP-FP-MSCYr8 Jan 2020

Adventure Lights Inc. 444 Beaconsfield Blvd. Beaconsfield, QC, Canada, H9W 4C1 (514) 694-8477





Guardian Trident Survival Water Activated Life Jacket Light

Olive Drab Case, Tan Bezel

Guardian Trident Survival Numbering System definition: (e.g. 58700 - GT - F - WP - 4 - WTIR - R - RP - FP - MSCT)

*Note: XX in place of character identifiers within the product number indicates not applicable or not used

58700 Guardian Trident Survival Base Number (Solas Tested)

GT	Body	CO	lor
91	Douy	CO	O

YY Yellow Case, Yellow Bezel
OY Orange Case, Yellow Bezel
OO Orange Case, Orange Bezel
OF YB Yellow Case, Black Bezel
TN Tan Case, Tan Bezel
OF Olive Drab Case, Olive Drab Bezel

GT

F Default Activation Pattern

BB

F Flashing 60Bpm

S Steady

WP Default Activation Principle

WA Water Activated (No Probe)
WP Water Activated with 35" Probe

Black Case, Black Bezel

WM Water Activated and Manual Override Plug

PP Pull-Pin

4 Rotary Switch Bezel Function

1 Fixed Bezel, 1 Function4 Rotating Bezel, 4 Function

WTIR LED output Color

WT White AM Amber WTIR White/IR

R Replaceable

R Replaceable BatteryD Disposable Unit

RP Reverse Polarity Program Switching

RP Yes XX No

FP Attachment Method

VC Velcro with Circular Strap FP Floating Patch VR Velcro with Rectangular Strap Helmet mount HM PC Plastic Clip VS Velcro Strap VΡ Velcro Patch VT Velcro with T-Strap

MSCY Locking Ring Clip

MSCT Tan Manual Safety Clip

MSCY Yellow Manual Safety Clip

Specifications subject to change without prior notice DOC. ID: P-PS-58700-OY-F-WP-4-WTIR-R-RP-FP-MSCYr8 Jan 2020