

## RED FLASH™

## Military Engine Start and Slave Battery Packs

As the choice of the UK Military for over 12 years now, our 12V and 24V engine slave start units have proved to be robust and reliable. Used by militaries around the world, our packs have supported operations in the cold Norwegian winters and hot desert sun both in Op Telic in Iraq and Op Herrick in Afghanistan. Used for starting a wide range of vehicles, including small and lightweight vehicles, armoured personnel carriers, battle tanks and light aircraft.

### Benefits

- Currently in service around the globe with operations in hot and cold climates
- Wide operating temperatures  $-40$  to  $+50^{\circ}\text{C}$
- Peak power 11.7kW
- Man portable
- Rugged for long life and durability
- A full range of approved output leads available



### Features

- Robust Polyethylene outer case, resistant to field and workshop damage
- Integral carry handle – suitable for use with a gloved hand
- LED state of charge indication
- Optional trolley
- NATO codified

[www.dmstech.co.uk](http://www.dmstech.co.uk)

Belbins Business Park, Cupernham Lane, Romsey, Hampshire, SO51 7JF, UK  
+44(0)1794 525400 sales@dmstech.co.uk

## Military Engine Start

**RF850**

**DMS Ref: 7204-0010**

**NSN : 6130-99-549-9700**

Including 1 x 2m 50mm<sup>2</sup> output lead fitted with fully insulated Crocodile Clips and 1 x 8A Charger

**RF24HD**

**DMS Ref: 7204-0011**

**NSN : 6130-99-736-6448**

Including 1 x 2m 50mm<sup>2</sup> output lead fitted with fully insulated Crocodile Clips, 1 x 2m 50mm<sup>2</sup> output lead fitted with NATO battle tank connector and 1 x 8A Charger

*Please see our accessories datasheet for available leads, connectors and trolleys.*

	RF 850	RF 24HD
Output Voltage - Nominal	12V	24V
Capacity	20Ah	26Ah
Peak Power @ 25°C	6.0kW	11.7kW
Cranking Performance @ 25°C	740A	785A
Weight – excluding external cables*	15kg	24kg
Dimensions (L x W x H)	360 x 190 x 510mm	
Case Construction	Black Polyethylene	
Safety Features	On/Off isolator switch Surge & spike protection Reverse polarity indication via audible alarm and LED Fitted with external accessible fuse Fully isolated output clamps	
Operating Temperature	-40 to +50°C	

*DMS technologies reserves the right to alter product specifications without prior notice*

*\* Weight of cables is dependant on connector type. Details are available on request.*



DMS technologies is a leading supplier of battery based electrical systems. We design, manufacture and supply high quality, reliable battery based power solutions to the Industrial, Automotive, Military and Telecoms markets. Our bespoke battery systems have been supplied to many Blue Chip engineering and defence companies world-wide.